

CoolPro

compressed air and gas aftercoolers
(air and water-cooled configurations)



PURE ENERGY



Purifying your compressed air,
increasing your efficiency.



Cooling, conditioning, purifying.

CoolPro

The Aftercooler market has gone through a profound change in recent years, with an ever increasing list of specific applications within both the air and gas fields requiring ever more sophisticated cooling solutions. MTA has fully met these elevated requirements, offering an extensive range of individual solutions to all User needs. And all this with MTA's trademark quality and technical expertise.



Robust industrial design

Only the highest quality materials are used, attentively selected and generously dimensioned to ensure years of trouble-free operation in even the harshest conditions. All models feature protective treatment and high quality painting processes. Air-cooled models include sturdy supporting legs.

Configurations for all needs

All material grades are offered, both for the air and water circuit, as are numerous configurations according to specific User requirements. Individual specifications as to operating pressures, temperatures and approvals can be catered for. Low pressure drop configurations are available.

Matching Separators

MTA Aftercoolers can be supplied either with or without matching Separators. As per the Aftercooler, so the Separator is also offered in numerous configurations and materials to cover all User needs, including models for higher pressures. High separation efficiencies are ensured, within an extremely reliable design.

Matching Drains

MTA offers an extensive range of Condensate Drains covering all User needs. Choose between mechanical zero-loss, electronic zero-loss, timed and manual drains, all featuring high grade materials and elevated peace of mind. All drain types can also be supplied in high pressure configurations.





LEADING AFTERCOOLER TECHNOLOGY

The Aftercooler market is changing; once strictly associated with the cooling of compressed air downstream of the Air Compressor, today the list of applications for Aftercoolers has grown significantly.

Many of these applications are very sophisticated in nature, and as a direct consequence the role of the Aftercooler itself has become ever more critical. The result is that a "standard" Aftercooler is no longer adequate to cover these elevated needs.

MTA, with over 25 years of experience in Aftercooler technology, has been a pioneer within this changing Aftercooler market. MTA is a supplier to many of the premier industries within numerous Aftercooler market sectors, working closely with its partners to satisfy their varied and individual needs.

So where does MTA Aftercooler technology excel?:

Application knowledge - Whatever your application, MTA can lead you to the optimum individual solution to your needs.

High quality design - At MTA no compromises are made when it comes to ensuring fail-safe design.

Advanced grade materials - Only the highest quality materials are utilised, both inside and out.

Precise manufacturing - Product quality is ensured thanks to MTA's manufacturing processes and expertise.

Flexibility to individual needs - As if the vast standard range were not enough, MTA is able to cater for all individual needs concerning materials used, configurations, and working limits.

Aftercoolers for all your individual applications

Complimentary water Chillers

In many cases the (water-cooled) Aftercooler also requires water cooling equipment, in the form of water chillers or water coolers. MTA is a world leader in chillers specifically for industrial applications. Consequently MTA is able to select and supply chiller/aftercooler packages according to specific customer requirements.

Typical technical gas applications:

- Oxygen (O₂)
- Hydrogen (H)
- Nitrogen (N)
- Methane (CH₄)
- CO₂
- Helium (He)
- Acetilene (C₂H₂)
- Ethylene (C₂H₄)
- Argon (Ar)

- Biogas
- CO
- Ethane
- Ammoniac
- Propane
- Other gases

Examples of other Aftercooler applications:

- Air compressors
- Intercoolers

- Portable Aftercoolers
- Pneumatic transport
- Turbine cooling
- Filter pre-cooling
- Adsorption dryer pre-cooling
- Low pressure drop dryers
- Plastics (PET / PEN)
- Shipbuilding
- Railways
- Truck cooling
- Glass industry
- Other applications






Cooling, conditioning, purifying.




WE / WF operation

Hot compressed air/gas passes through the tubes. Cooling water passes around the tubes in counterflow, guided by baffles which increase the cooling effect. The air/gas cools and liquid condensate is formed. The condensate is efficiently removed by a Separator downstream of the Aftercooler.



AF operation

Hot compressed air/gas passes through the tubes. Ambient cooling air is forced across the tubes by the fan, with the fins increasing the cooling effect. The air/gas cools and liquid condensate is formed. The condensate is efficiently removed by a Separator downstream of the Aftercooler.



PRODUCT SPECIFICATIONS

Water-cooled Aftercoolers:

Features:

- Fixed (WF) or removable (WE) tube bundle.
- Threaded and flanged models.
- Horizontal and vertical configurations available.
- Performance enhancing ribbed tubing fitted as standard (straight tubing available for low pressure drop applications).

Materials:

- Carbon steel vessel with copper tubes (standard configuration).
- Carbon steel vessel with stainless steel AISI304 or AISI316 tubes.
- Completely in stainless steel AISI304 or AISI316.
- Completely in Cupro-nickel.

Operating limits:

- Max. pressure: standardly 16 or 10 bar(g) depending on model, optionally up to 250bar(g).
- Max. temperature: standardly 200 °C, higher on request.

Approvals:

- PED, ASME, SELO, TEMA; others on request.

Air-cooled Aftercoolers:

Features:

- Generous heat exchanger dimensioning for increased efficiency.
- Threaded and flanged models.
- Protective grilles.
- Robust casing and legs.
- Low noise lubricated fan.

Materials:

- Cooling coil with copper tubes and aluminium fins.
- Casing and legs in painted and galvanized steel.

Operating limits:

- Max. pressure: standardly 16 or 10 bar(g) depending on model, optionally up to 40 bar(g).
- Max. temperature: 200°C.

Approvals:

- PED; others on request.

Separators:

Features:

- Near 100% separation efficiency with low pressure drops.
- Threaded and flanged models.
- Horizontal and vertical configurations available.
- Various condensate drains available.
- Thermometer supplied from 27,0 m³/min.

Configurations:

- Centrifugal (standard configuration).
- Double or single demister (in stainless steel AISI304).
- Finned pack.

Materials:

- AS: aluminium (DURACHROM plated and passivated).
- MS: - carbon steel (standard configuration).
- stainless steel AISI304 or AISI316.




Operating limits:

- Max. pressure: standardly 16 or 10 bar(g) according to model, optionally up to 250 bar(g).
- Max. temperature: standardly 65°C, higher on request.




Approvals:

- PED, ASME, SELO; others on request.




model	airflow		matching separator	connections				dimensions (mm)					weight (kg)	
	m ³ /h	m ³ /min		air in/out no sep.	air out with sep.	water in/out	cond. (ØA)	A	B	C	D	E	WF only	WF + sep.
WF015	90	1.5	AS035	1"	1/2"	3/8"	1/2"	894	260	103	600	/	3.4	4.5
WF027	162	2.7	AS080	1 1/2"	1"	1/2"	1/2"	941	263	108	600	/	6.3	9.1
WF042	252	4.2	AS080	1 1/2"	1"	1/2"	1/2"	941	263	108	600	/	7.1	9.9
WF074	445	7.4	MS105	2"	2"	3/4"	1/2"	1.087	385	135	600	/	12	17.5
WF105	630	10.5	MS105	2"	2"	3/4"	1/2"	1.087	385	135	600	/	13	18.5
WF125	750	12.5	MS165	2 1/2"	2 1/2"	1"	1"	1.782	685	200	1.100	/	25	45
WF165	990	16.5	MS165	2 1/2"	2 1/2"	1"	1"	1.782	685	200	1.100	/	28	48
WF225	1.350	22.5	MS270	DN80	DN80	1"	1"	1.999	685	205	1.100	/	40	64
WF270	1.620	27	MS270	DN80	DN80	1"	1"	1.999	685	205	1.100	/	44	68
WF350	2.100	35	MS450	DN125	DN125	1 1/4"	1"	1.859	835	100	1.100	/	52	100
WF450	2.700	45	MS450	DN125	DN125	1 1/4"	1"	1.859	835	100	1.100	/	57	105
WF570	3.420	57	MS800	DN150	DN150	1 1/4"	1"	1.959	1.000	100	1.100	/	70	140
WF800	4.800	80	MS800	DN200	DN150	1 1/4"	1"	2.144	1.000	100	1.100	175	93	163
WF1030	6.180	103	MS1250	DN200	DN200	1 1/4"	2"	2.083	1.240	100	1.100	/	121	225
WF1250	7.500	125	MS1250	DN250	DN200	1 1/4"	2"	2.311	1.240	100	1.100	200	140	244
WF1800	10.800	180	MS1800	DN300	DN250	2"	2"	2.513	1.600	100	1.100	225	181	355
WF2500	15.000	250	MS3800	DN350	DN300	DN65	2"	2.638	1.930	125	1.050	350	252	507
WF3800	22.800	380	MS3800	DN450	DN300	DN80	2"	2.697	1.930	125	1.050	400	356	611
WF5200	31.200	520	MS6400	DN500	DN400	DN100	1"	3.039	2.420	125	1.050	530	450	880
WF6400	38.400	640	MS6400	DN600	DN400	DN100	1"	3.094	2.420	125	1.050	530	560	990




model	airflow		matching separator	connections				dimensions (mm)					weight (Kg)	
	m ³ /h	m ³ /min		air in/out no sep.	air out with sep.	water in/out	cond. (ØA)	A	B	C	D	E	WE only	WE + sep.
WE074	445	7.4	MS105	2"	1 1/2"	3/4"	1/2"	1.120	385	104	520	/	29	34,5
WE105	630	10.5	MS105	2"	2"	3/4"	1/2"	1.120	385	104	520	/	30	35,5
WE125	750	12.5	MS165	2 1/2"	2 1/2"	1"	1"	1.170	685	127	1.050	/	45	65
WE165	990	16.5	MS165	2 1/2"	2 1/2"	1"	1"	1.170	685	127	1.050	/	46	66
WE225	1.350	22.5	MS270	DN80	DN80	1"	1"	1.974	685	217	1.300	/	75	99
WE270	1.620	27	MS270	DN80	DN80	1"	1"	1.974	685	217	1.300	/	76	100
WE350	2.100	35	MS450	DN125	DN125	1 1/4"	1"	1.855	835	125	1.050	/	57	105
WE450	2.700	45	MS450	DN125	DN125	1 1/4"	1"	1.855	835	125	1.050	/	61	109
WE570	3.420	57	MS800	DN150	DN150	1 1/4"	1"	1.955	1.000	125	1.050	/	75	145
WE800	4.800	80	MS800	DN200	DN150	1 1/4"	1"	2.139	1.000	125	1.050	179	96	166
WE1030	6.180	103	MS1250	DN200	DN200	1 1/4"	2"	2.079	1.240	125	1.050	/	128	232
WE1250	7.500	125	MS1250	DN250	DN200	1 1/4"	2"	2.289	1.240	118	1.050	204	146	250
WE1800	10.800	180	MS1800	DN300	DN250	2"	2"	2.180	1.600	118	1.050	229	190	364
WE2500	15.000	250	MS3800	DN350	DN300	DN65	2"	2.694	1.930	158	980	354	274	529
WE3800	22.800	380	MS3800	DN450	DN300	DN80	2"	2.747	1.930	158	980	404	399	654
WE5200	31.200	520	MS6400	DN500	DN400	DN100	1"	3.185	2.420	158	980	534	502	932
WE6400	38.400	640	MS6400	DN600	DN400	DN100	1"	3.189	2.420	158	980	534	613	1.043



model	airflow		matching separator	connections				Q min.	dimensions (mm)					weight (Kg)	
	m ³ /h	m ³ /min		air in/out only AF	air out with sep.	cond. (ØA)	A		B	C	D	E	AF only	AF + sep.	
AF007	36	0,6	AS035	3/4"	1/2"	1/2"	500	769	510	523	435	750	16	17,1	
AF013	72	1,2	AS035	3/4"	1/2"	1/2"	500	769	510	523	435	750	18	19,1	
AF025	144	2,4	MS042	1 1/4"	1 1/4"	1/2"	700	870	520	766	600	842	24	27,5	
AF037	216	3,6	MS042	1 1/4"	1 1/4"	1/2"	700	870	520	766	600	842	26	29,5	
AF055	324	5,4	MS105	2"	2"	1/2"	1.200	1.200	529	1.008	770	1.083	39	44,5	
AF086	510	8,5	MS105	2"	2"	1/2"	1.200	1.120	529	1.008	770	1.083	40	45,5	
AF121	720	12,0	MS165	2 1/2"	2 1/2"	1"	1.700	1.570	737	1.205	900	1.525	86	106	
AF161	960	16,0	MS165	2 1/2"	2 1/2"	1"	1.700	1.570	737	1.205	900	1.525	88	108	
AF201	1.200	20,0	MS165	2 1/2"	2 1/2"	1"	1.700	1.570	737	1.205	900	1.525	90	110	
AF251	1.613	26,8	MS450	DN125	DN125	1"	1.800	1.501	686	1.568	1.404	1.364	242	290	
AF381	2.323	38,7	MS450	DN150	DN125	1"	2.300	1.900	780	1.818	1.654	1.663	262	320	



- Airflow refers to the following conditions: air FAD 20 °C/1 barA, air inlet temperature 120 °C, ambient temperature 20 °C, air outlet temperature 10 °C above water (air) inlet temperature, pressure 7 bar(g).
- Maximum working pressure: 16 bar(g) (WF015-1030 / WE074-1030 / all AF) and 10 bar(g) (WF1250-6400 / WE 1250-6400).
- WE / WF are supplied with a nipple (WF 015-165 / WE 074-165) or with counterflanges (WF225-6400 / WE225-6400).
- AF power supply: 230V±10%/1Ph/50 Hz (AF007-013); 400V ±10% /3Ph/50 Hz (AF025-381).
- WE / WF supplied with separator includes the connecting kit. The condensate drain must be ordered separately.
- AF supplied with separator doesn't include the matching nipple or counterflanges. The condensate drain must be ordered separately.
- WF / WE versions for vertical installation are available on request.
- All models are CE approved and conform to PED directive 97/23/CE where applicable. Other approvals available on request.






PURE INNOVATION, PURE SATISFACTION, PURE ENERGY

MTA was born over 25 years ago with a clear objective: improving mankind's relationship with two distinct natural resources, air and water, and optimising their transformation into energy sources. Our investment in Innovation ensures we offer the very latest technologies, whilst an expert team worldwide ensures our Customers achieve the highest levels of Satisfaction. At MTA energy is our business, and improving your relationship with your energy is our aim.



STRATEGIC DIVERSIFICATION

MTA covers three distinct market segments. As well as Compressed Air & Gas Treatment solutions, we offer a complete series of products for the Industrial Process Cooling market, as well as an extensive range of Air Conditioning products. MTA has always been known for the innovation it has brought into each of these three sectors; in fact our strategic diversification offers our Customers unique benefits unseen in their individual fields.



FAR REACHING BUT ALWAYS CLOSE BY

MTA is officially represented in some 60 countries worldwide. 8 MTA Sales Companies cover 4 continents. Our staff and representatives boast expert knowledge and benefit from continuous training. Accurate attention to service support guarantees that our Customers can look forward to long term peace of mind and an optimized energy solution. We always remain close to our Customers, so wherever you may be, we will be near to you.

The data contained herein is not binding. With a view to continuous improvement, MTA reserves the right to make changes without prior notice. Please contact our sales office for further information. Reproduction in whole or in part is forbidden.

www.mta-it.com

M.T.A. S.p.A.

Viale Spagna, 8 - ZI
35020 Tribano (PD) - Italy
Tel. +39 049 9588611
info@mta-it.com

Compressed air treatment
Fax +39 049 9588612

Process cooling
Fax +39 049 9588661

Air conditioning
Fax +39 049 9588604

MTA is represented in some 60 countries worldwide. For information concerning your nearest MTA representative please contact M.T.A. S.p.A.

MTA Australasia
tel. +61 3 9702 4348
www.mta-au.com

MTA Cina
tel. +86 21 5417 1080
www.mta-it.com.cn

MTA Francia
tel. +33 04 7249 8989
www.mtafrance.fr

MTA Germania
tel. +49 2163 5796-0
www.mta.de

MTA Romania
tel. +40 368 457 004
www.mta-it.ro

MTA Spagna
tel. +34 938 281 790
www.novair.es

MTA USA
tel. +1 716 693 8651
www.mta-it.com